


900 Series
Fry-tops 900
GAS FRY-TOP, FTG9-05 VL
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,30

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	9,34
	Kcal/h	8.032,40
LPG	Consumption (kg/h)	0,74
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,95
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-05 VL

Made of stainless steel.

Smooth hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.

Safety valve and thermocouple.

Fat collector under the grill.


Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG9-05 VR

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,30

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	9,34
	Kcal/h	8.032,40
LPG	Consumption (kg/h)	0,74
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,95
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-05 VR

Made of stainless steel.

Ribbed hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.

Safety valve and thermocouple.

Fat collector under the grill.


Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP, FTG9-05 L
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,30

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	9,34
	Kcal/h	8.032,40
LPG	Consumption (kg/h)	0,74
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,95
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-05 L

Made of stainless steel.

Smooth hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP, FTG9-05 R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,30

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	9,34
	Kcal/h	8.032,40
LPG	Consumption (kg/h)	0,74
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,95
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-05 R

Made of stainless steel.

Ribbed hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP, FTG9-10 VL
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	18,68
	Kcal/h	16.064,80
LPG	Consumption (kg/h)	1,48
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,90
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-10 VL

Made of stainless steel.

Smooth hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Safety valves and thermocouples.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG9-10 VR

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	18,68
	Kcal/h	16.064,80
LPG	Consumption (kg/h)	1,48
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,90
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-10 VR

Made of stainless steel.

Ribbed hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Safety valves and thermocouples.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP, FTG9-10 V L+R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	18,68
	Kcal/h	16.064,80
LPG	Consumption (kg/h)	1,48
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,90
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-10 V L+R

Made of stainless steel.

2/3 smooth + 1/3 ribbed hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Safety valves and thermocouples.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP, FTG9-10 L
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	18,68
	Kcal/h	16.064,80
LPG	Consumption (kg/h)	1,48
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,90
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-10 L

Made of stainless steel.

Smooth hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP, FTG9-10 L+R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	18,68
	Kcal/h	16.064,80
LPG	Consumption (kg/h)	1,48
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,90
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-10 L+R

Made of stainless steel.

2/3 smooth & 1/3 ribbed hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG9-10 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	18,68
	Kcal/h	16.064,80
LPG	Consumption (kg/h)	1,48
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,90
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG9-10 R

Made of stainless steel.

Ribbed hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG/C9-05 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	80,00
Volumen	m3	0,12	0,30

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	9,34
	Kcal/h	8.032,40
LPG	Consumption (kg/h)	0,74
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,95
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG/C9-05 L

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate. Smooth hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG/C9-05 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	510,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,30

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	9,34
	Kcal/h	8.032,40
LPG	Consumption (kg/h)	0,74
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	0,95
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG/C9-05 R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate. Ribbed hot-plate. Surface area: 24 dm2.

Burner in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 9,34 kW.

Dimensions: 425 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	365	738	147	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP, FTG/C9-10 L
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

Not used		0,00
----------	--	-------------

WATER

Not used

GAS

Power	KW	18,68
	Kcal/h	16.064,80
LPG	Consumption (kg/h)	1,48
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,90
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG/C9-10 L

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate. Smooth hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP, FTG/C9-10 L+R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	18,68
	Kcal/h	16.064,80
LPG	Consumption (kg/h)	1,48
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,90
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG/C9-10 L+R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate. 2/3 smooth & 1/3 ribbed hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

GAS FRY-TOP, FTG/C9-10 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	128,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

Not used		0,00
----------	--	-------------

WATER

Not used

GAS

Power	KW	18,68
	Kcal/h	16.064,80
LPG	Consumption (kg/h)	1,48
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,90
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP, FTG/C9-10 R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate. Ribbed hot-plate. Surface area: 50 dm2.

Burners in stainless steel with pilot.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.


Power: 2 x 9,34 kW = 18,68 kW.

Dimensions: 850 x 900 x 290 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	790	738	147	R.3/4"G	Prever regulador y llave de corte individual





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE9-05 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	505,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,29

ELECTRICITY

<u>Electric power</u>	KW	6,00
230V - I+N		2x4+T - 32 A
230V - III		3x2,5+T - 20 A
400V - III+N		4x1,5+T - 16 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE9-05 L

Made of stainless steel.

Smooth hot-plate. Surface area: 24 dm².

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 6000 W.

Dimensions: 425 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	250	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE9-05 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	505,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,29

ELECTRICITY

<u>Electric power</u>	KW	6,00
230V - I+N		2x4+T - 32 A
230V - III		3x2,5+T - 20 A
400V - III+N		4x1,5+T - 16 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE9-05 R

Made of stainless steel.

Ribbed hot-plate. Surface area: 24 dm².

Shielded elements in stainless steel for heating.

Thermostat control of the hot-plate temperature 120 C° -310 C°.


Fat collector under the grill.

Power: 6000 W.

Dimensions: 425 x 900 x 290 mm.

Connections points

	X	Y	Z	Diameter	Information
ELECTRICITY	250	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE9-10 L

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

<u>Electric power</u>	KW	12,00
230V - I+N		2x10+T - 100 A
230V - III		3x6+T - 63 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE9-10 L

Made of stainless steel.

Smooth hot-plate. Surface area: 50 dm².

Shielded elements in stainless steel for heating.

Thermostat control of the hot-plate temperature 120 C° -310 C°.


Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points

	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial




900 Series
Fry-tops 900
ELECTRIC FRY-TOP, FTE9-10 L+R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

<u>Electric power</u>	KW	12,00
230V - I+N		2x10+T - 100 A
230V - III		3x6+T - 63 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE9-10 L+R

Made of stainless steel.

2/3 smooth & 1/3 ribbed hot-plate. Surface area: 50 dm2.

Shielded elements in stainless steel for heating.

Thermostat control of the hot-plate temperature 120 C° -310 C°.


Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points

	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial





900 Series

Fry-tops 900

ELECTRIC FRY-TOP, FTE9-10 R

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

<u>Electric power</u>	KW	12,00
230V - I+N		2x10+T - 100 A
230V - III		3x6+T - 63 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE9-10 R

Made of stainless steel.

Ribbed hot-plate. Surface area: 50 dm².

Shielded elements in stainless steel for heating.

Thermostat control of the hot-plate temperature 120 C° -310 C°.


Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points

	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial




900 Series
Fry-tops 900
ELECTRIC FRY-TOP, FTE/C9-05 L
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	505,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,29

ELECTRICITY

<u>Electric power</u>	KW	6,00
230V - I+N		2x4+T - 32 A
230V - III		3x2,5+T - 20 A
400V - III+N		4x1,5+T - 16 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE/C9-05 L

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate.

Smooth hot-plate. Surface area: 24 dm².

Shielded elements in stainless steel for heating.


Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 6000 W.

Dimensions: 425 x 900 x 290 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	250	125	50		Prever Interruptor diferencial




900 Series
Fry-tops 900
ELECTRIC FRY-TOP, FTE/C9-05 R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	425,00	505,00
Depth	mm	900,00	990,00
Height	mm	320,00	590,00
Weigth	Kg	70,00	88,00
Volumen	m3	0,12	0,29

ELECTRICITY

<u>Electric power</u>	KW	6,00
230V - I+N		2x4+T - 32 A
230V - III		3x2,5+T - 20 A
400V - III+N		4x1,5+T - 16 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE/C9-05 R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate.

Ribbed hot-plate. Surface area: 24 dm2.

Shielded elements in stainless steel for heating.

Thermostat control of the hot-plate temperature 120 C° -310 C°.


Fat collector under the grill.

Power: 6000 W.

Dimensions: 425 x 900 x 290 mm.

Connections points

	X	Y	Z	Diameter	Information
ELECTRICITY	250	125	50		Prever Interruptor diferencial




900 Series
Fry-tops 900
ELECTRIC FRY-TOP, FTE/C9-10 L
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

<u>Electric power</u>	KW	12,00
230V -1+N		2x10+T - 100 A
230V - III		3x6+T - 63 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE/C9-10 L

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate.

Smooth hot-plate. Surface area: 50 dm2.

Shielded elements in stainless steel for heating.

Thermostat control of the hot-plate temperature 120 C° -310 C°.


Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points

	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial




900 Series
Fry-tops 900
ELECTRIC FRY-TOP, FTE/C9-10 L+R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

<u>Electric power</u>	KW	12,00
230V - I+N		2x10+T - 100 A
230V - III		3x6+T - 63 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE/C9-10 L+R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate.

2/3 smooth & 1/3 ribbed hot-plate. Surface area: 50 dm2.

Shielded elements in stainless steel for heating.

Thermostat control of the hot-plate temperature 120 C° -310 C°.


Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points

	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial




900 Series
Fry-tops 900
ELECTRIC FRY-TOP, FTE/C9-10 R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	930,00
Depth	mm	900,00	990,00
Height	mm	320,00	620,00
Weigth	Kg	120,00	149,00
Volumen	m3	0,24	0,57

ELECTRICITY

<u>Electric power</u>	KW	12,00
230V - I+N		2x10+T - 100 A
230V - III		3x6+T - 63 A
400V - III+N		4x2,5+T - 32 A

WATER

Not used

GAS

Not used

STEAM

Not used

AIR

Not used

ELECTRIC FRY-TOP, FTE/C9-10 R

Made of stainless steel.

50 microns thickness chromium coated steel sheeting hot-plate.

Ribbed hot-plate. Surface area: 50 dm2.

Shielded elements in stainless steel for heating.

Thermostat control of the hot-plate temperature 120 C° -310 C°.


Fat collector under the grill.

Power: 12000 W.

Dimensions: 850 x 900 x 290 mm.

Connections points

	X	Y	Z	Diameter	Information
ELECTRICITY	675	125	50		Prever Interruptor diferencial




900 Series
Fry-tops 900
GAS FRY-TOP WITH OVEN, FTG9-11 L
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	27,28
	Kcal/h	23.460,80
LPG	Consumption (kg/h)	2,26
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	2,87
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

Certificate EQNET- CE

99AP56

GAS FRY-TOP WITH OVEN, FTG9-11 L

Made of stainless steel.

Smooth hot-plate. Surface area: 50 dm2.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.

Pilot and thermocouple.


Thermostatic control (130 C° - 350 C°).

Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

Connections points

	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP WITH OVEN, FTG9-11 L+R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	27,28
	Kcal/h	23.460,80
LPG	Consumption (kg/h)	2,26
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	2,87
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP WITH OVEN, FTG9-11 L+R

Made of stainless steel.

2/3 Smooth + 1/3 Ribbed hot-plate. Surface area: 50 dm2.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.

Pilot and thermocouple.

Thermostatic control (130 C° - 350 C°).


Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP WITH OVEN, FTG9-11 R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	27,28
	Kcal/h	23.460,80
LPG	Consumption (kg/h)	2,26
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	2,87
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP WITH OVEN, FTG9-11 R

Made of stainless steel.

Ribbed hot-plate. Surface area: 50 dm2.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.

Pilot and thermocouple.

Thermostatic control (130 C° - 350 C°).


Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP WITH OVEN, FTG/C9-11 L
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	27,28
	Kcal/h	23.460,80
LPG	Consumption (kg/h)	2,26
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	2,87
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP WITH OVEN, FTG/C9-11 L

Made of stainless steel.

Smooth hot-plate. Surface area: 50 dm2.

50 microns thickness chromium coated steel sheeting hot-plate.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.

Pilot and thermocouple.

Thermostatic control (130 C° - 350 C°).


Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP WITH OVEN, FTG/C9-11 L+R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	27,28
	Kcal/h	23.460,80
LPG	Consumption (kg/h)	2,26
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	2,87
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP WITH OVEN, FTG/C9-11 L+R

Made of stainless steel.

2/3 Smooth + 1/3 Ribbed hot-plate. Surface area: 50 dm2.

50 microns thickness chromium coated steel sheeting hot-plate.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.

Pilot and thermocouple.

Thermostatic control (130 C° - 350 C°).


Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual




900 Series
Fry-tops 900
GAS FRY-TOP WITH OVEN, FTG/C9-11 R
DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	850,00	890,00
Depth	mm	900,00	1.045,00
Height	mm	850,00	1.150,00
Weigth	Kg	195,00	219,00
Volumen	m3	0,65	1,07

ELECTRICITY

Not used			0,00
----------	--	--	-------------

WATER

Not used

GAS

Power	KW	27,28
	Kcal/h	23.460,80
LPG	Consumption (kg/h)	2,26
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	2,87
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS FRY-TOP WITH OVEN, FTG/C9-11 R

Made of stainless steel.

Ribbed hot-plate. Surface area: 50 dm2.

50 microns thickness chromium coated steel sheeting hot-plate.

Burner in stainless steel with pilot.

Power of burners: 2 x 9,34 kW.

Piezoelectric burner ignition.

Thermostat control of the hot-plate temperature 120 -310 C°.

Fat collector under the grill.

2/1 GN oven made of stainless steel, with burner in stainless steel. Oven power: 8.6 kW.

Pilot and thermocouple.

Thermostatic control (130 C° - 350 C°).

Total power: 27,28 kW

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP56

Connections points	X	Y	Z	Diameter	Information
GAS	805	635	105	R.3/4"G	Prever regulador y llave de corte individual

